Page 1 of 2

Borehole

RUST GEOTECH INC.

41-10-05

Log Event A

Borehole Information

Site Number : 299-W23-82 Farm: SXTank: SX-110

TOC Elevation: 663.34 W-Coord: 75,638 N-Coord: 35,206

Date Drilled: 2/26/1962 Water Level, ft:

Casing Record

Type: Steel-welded Thickness: 0.280 ID, in.: 6

Top Depth, ft.: Bottom Depth, ft. : 0

Equipment Information

Detector Type: HPGe Logging System: 1 **Detector Efficiency:** 35.0 %

Calibration Date: 03/1995 Calibration Reference : GJPO-HAN-1

Logging Information

Logging Engineer: Gary Lekvold Log Run Date : Log Run Number: 1 6/21/1995

Start Depth, ft.: 0.0 Counting Time, sec.: 100 L/R: L Shield: N Finish Depth, ft.: 20.5 MSA Interval, ft. : 0.5 Log Speed, ft/min.: <u>n/a</u>

Logging Engineer: Gary Lekvold Log Run Number: 2 Log Run Date: 6/22/1995

Start Depth, ft.: 19.5 Counting Time, sec.: 100 L/R: L Shield: N Finish Depth, ft. : 45.0 MSA Interval, ft.: Log Speed, ft/min.:

Logging Engineer: Gary Lekvold Log Run Number : 3 Log Run Date: 6/22/1995

Start Depth, ft.: 74.5 Counting Time, sec.: 100 L/R: L Shield: N Finish Depth, ft.: 44.0 MSA Interval, ft. : 0.5 Log Speed, ft/min.: <u>n/a</u>



Spectral Gamma-Ray Borehole Log Data Report

Page 2 of 2

Borehole 41-10-05

Log Event A

Analysis Information

Analyst: S.E. Kos

Data Processing Reference : <u>Data Analysis Manual Ver. 1</u> Analysis Date : <u>11/6/1995</u>

Analysis Notes:

This borehole was logged in three log runs. The pre- and post- field verification spectra indicated that the logging system was operating properly during data collection. The energy/channel drift observed during the log runs exceeded the search parameters of the data processing software; therefore, several energy calibrations of the log spectra were required to process the data.

The casing thickness is 1/4 in.(0.250 in.); the casing correction used to process the data was for 1/4-in.-thick casing. The borehole was dry and no water correction was required.

The only man-made radionuclide identified was Cs-137. This contaminant was identified from the surface to a depth of about 11.5 ft, at a few intermittent locations, and at the bottom of the borehole.

Details regarding the interpretation of the data for this borehole are presented in the Tank Summary Data Reports for tanks SX-110 and SX-113.

Log Plot Notes:

Three log plots are provided. The Cs-137 activity is plotted on a separate plot to provide details of activity and distribution.

The natural gamma-ray logs show the activities of the naturally occurring radionuclides potassium (K-40), uranium (U-238), and thorium (Th-232). The KUT plot is provided to allow correlation of lithologic features between boreholes. The KUT activities observed in this borehole are typical for Hanford Site sediments.

A combination plot incorporates the Cs-137 and KUT log data with the total gamma-ray count rate derived from the spectral gamma-ray data and the gross gamma-ray data acquired with the WHC Tank Farms gross gamma-ray logging systems. This plot allows correlation of the Cs-137 contamination zones with lithologic features and with the historical gross gamma-ray record.

The statistical uncertainty in a measurement is represented on the log plots by uncertainty bars where appropriate. This uncertainty is reported at the 95-percent confidence interval. The minimum detectable activity (MDA) of a radionuclide represents the lowest activity at which positive identification of a gamma-ray peak is statistically defensible. The MDA values are indicated on the log plots by open circles. If the reported activity is slightly above the MDA, the 95-percent confidence interval may extend below the MDA value and the measurement cannot be stated with 95-percent confidence.

The Tank Farms gross gamma-ray plot is produced from the most recent data available from WHC. No corrections other than scale adjustments for plotting have been made to the data.